MACHEREY-NAGEL



Data sheet

28.12.2019

Filter paper

Parameter*	Value*
Grade	MN 1640 w
Basis weight	85 g/m²
Thickness	0.2 mm
Filtration speed	9 s
Surface	smooth / glatt
Ash content	<0.01 %
Average retention capacity	7-12 μm
Application	Ashless, wet-strengthened, fast filtration, for coarse precipitates

www.mn-net.com

US:



MACHEREY-NAGEL GmbH & Co. KG \cdot Neumann-Neander-Str. 6–8 \cdot 52355 Düren \cdot Germany

DE/international: CH: FR:

Tel.: +49 24 21 969-0 Tel.: +41 62 388 55 00 Tel.: +33 388 68 22 68 Tel.: +1 484 821 0984

Fax: +49 24 21 969-199 Fax: +41 62 388 55 05 Fax: +33 388 51 76 88 Fax: +1 484 821 1272

E-mail: info@mn-net.com E-mail: sales-ch@mn-net.com E-mail: sales-sr@mn-net.com E-mail: sales-sr@mn-net.com

^{*}These data are typical values and must not be regarded as specification.

MACHEREY-NAGEL



Data sheet

www.mn-net.com

US:



MACHEREY-NAGEL GmbH & Co. KG \cdot Neumann-Neander-Str. 6–8 \cdot 52355 Düren \cdot Germany

DE/international: CH: FR:

Tel.: +49 24 21 969-0 Tel.: +41 62 388 55 00 Tel.: +33 388 68 22 68 Tel.: +1 484 821 0984
Fax: +49 24 21 969-199 Fax: +41 62 388 55 05 Fax: +33 388 51 76 88 Fax: +1 484 821 1272
E-mail: info@mn-net.com E-mail: sales-ch@mn-net.com E-mail: sales-fr@mn-net.com E-mail: sales-us@mn-net.com

^{*}These data are typical values and must not be regarded as specification.